



MPS ServiceNet

[About MPS](#)
[Technical References](#)
[Customer Service](#)
[Distributor Locator](#)
[Rep Locator](#)
[Industry Links](#)
[News](#)
[Contact Us](#)

Login

- enter email -
- enter password -

Search

Cross Reference

Keyword or Part #

Pole Line Hardware A-E >> Bolts

Machine

[Print This Page](#)
[Print PDF Catalog Page\(s\)](#)



Features:

- Square Head and Square Nut
- Roll threaded.
- Bolts 1/2-inch and larger in diameter and 7-inch and longer in length also have cone points which permit driving without damage to the threads.

Material:

- Hot Dip Galvanized

[Check out the highly corrosion resistant options with TDG protection.](#)

Online Catalog

MacLean Real-Time Design™

Anchors - Utility

Arresters

Conductor Hardware

Cutouts

Fiberglass - Utility

Safety Products

Transmission Insulators

Distribution Insulators

Substation Insulators

Pole Line Hardware A-E

Pole Line Hardware F-Z

Industry Links

Buy America Certified

Also of Interest

Arresters

Conductor Hardware

Transmission Insulators

3/8 Inch Diameter - Minimum Tensile Strength 4,250 Lbs.			
Catalog Number	Bolt Length 'L' (Inches)	Thread Length 'T' (Inches)	Weight/100 (lbs)
J8603	3	1	13
J8604	4	3	15
J8604-1/2	4-1/2	3	17
J8605	5	3	18
J8606	6	3	21
J8608	8	4	27
J8610	10	4	32

1/2 Inch Diameter - Minimum Tensile Strength 8,500 Lbs.			
Catalog Number	Bolt Length 'L' (Inches)	Thread Length 'T' (Inches)	Weight/100 (lbs)
J8701-1/2	1-1/2	1-1/4	18
J8702	2	1-1/4	20
J8702-1/2	2-1/2	1-1/4	23
J8703	3	1-1/4	25
J8704	4	3	31
J8705	5	3	36
J8706	6	3	41
J8707	7	4	48
J8708	8	4	50
J8709	9	4	57
J8710	10	6	60
J8712	12	6	70
J8714	14	6	79
J8716	16	6	89

5/8 Inch Diameter - Minimum Tensile Strength 13,550 Lbs.			
Catalog Number	Bolt Length 'L' (Inches)	Thread Length 'T' (Inches)	Weight/100 (lbs)
J8801-1/2	1-1/2	1-1/4	30
J8802	2	1-1/2	34
J8802-1/2	2-1/2	1-1/2	38
J8803	3	1-1/2	44
J8804	4	3	50
J8805	5	3	57
J8806	6	3	62
J8807	7	4	72

J8808	8	4 or 6	82
J8809	9	4 or 6	88
J8810	10	6	94
J8812	12	6	108
J8814	14	6	125
J8816	16	6	136
J8818	18	6	152
J8820	20	6	170
J8822	22	6	184
J8824	24	6	200
J8826	26	6	224
J8828	28	6	242

3/4 Inch Diameter - Minimum Tensile Strength 20,050 Lbs.			
Catalog Number	Bolt Length 'L' (Inches)	Thread Length 'T' (Inches)	Weight/100 (lbs)
J8902	2	1-3/4	57
J8903	3	1-3/4	67
J8906	6	4	101
J8908	8	4	118
J8910	10	6	142
J8912	12	6	162
J8914	14	6	188
J8916	16	6	212
J8918	18	6	228
J8920	20	6	252
J8922	22	6	268
J8924	24	6	296
J8926	26	6	316
J8928	28	6	344

7/8 Inch Diameter - Minimum Tensile Strength 27,700 Lbs.			
Catalog Number	Bolt Length 'L' (Inches)	Thread Length 'T' (Inches)	Weight/100 (lbs)
J9062	12	6	240
J9064	14	6	264
J9066	16	6	288
J9068	18	6	320
J9070	20	6	345
J9072	22	6	380
J9074	24	6	430
J9076	26	6	442