Distributor Locator

Rep Locator

Industry Links News

Contact Us



Forgot your password?

- enter password -

Need an account?

Print This Page Print PDF Catalog Page(s)

Pole Line Hardware F-Z >> Pins

% Online Catalog

MacLean Real-Time Design™

Anchors - Utility

Arresters

Conductor Hardware

Cutouts

Fiberglass - Utility

Safety Products

Transmission Insulators

Distribution Insulators

Substation Insulators

Pole Line Hardware A-

Pole Line Hardware F-

Industry Links

Buy America Certified


Features:


Crossarm

- Crossarm Pins are forged in one piece from alloy steel
- Large bases distribute loads without crushing flat wood crossarms.
- A square wrenching shoulder is provided above the base for rotating the insulator groove into position.
- Long shank pins come complete with a square washer, square nut and concave locknut.
- Short shank pins for steel crossarms are furnished with a square nut and split coil lockwasher.

Material:

- Pins have a 1" ANSI standard nylon alloy or cast lead threads for pin type insulators.
- Pins with a "Z" suffix in the catalog number are furnished with insulator threads produced from an advanced nylon alloy compound.
- Body: Hot Dip Galvanized





Short Shank Pins

Also of Interest

Conductor Hardware

Anchors - Utility

Transmission Insulators

| Long Shank- For Insulators with Standard 1: Threaded Pin Hole | | | | | | | | | |
|---|-----------------|-----|---|-------|-------|---|--------------------------|------------------|--|
| Catalog Number | Thread Material | S | Α | В | Т | D | Washer Dim. (Sq. Inches) | Weight/100 (lbs) | |
| J203Z | Nylon Alloy | 5/8 | 5 | 5-3/4 | 4 | 2 | 2 | 138 | |
| J204Z | Nylon Alloy | 5/8 | 5 | 6-1/2 | 4 | 2 | 2 | 144 | |
| J2802Z | Nylon Alloy | 5/8 | 5 | 8 | 4 | 2 | 1-3/4 (round) | 157 | |
| J206Z | Nylon Alloy | 5/8 | 6 | 5-3/4 | 2-3/4 | 2 | 2 | 147 | |
| J207Z | Nylon Alloy | 5/8 | 6 | 6-1/2 | 3 | 2 | 2 | 151 | |
| JP40581Z | Nylon Alloy | 5/8 | 6 | 7-1/2 | 3-1/4 | 2 | 2 | 200 | |
| <u>J211Z</u> | Nylon Alloy | 3/4 | 6 | 6-1/2 | 3-1/4 | 2 | 2-1/4 | 232 | |
| J22267Z | Nylon Alloy | 3/4 | 6 | 8 | 4-1/2 | 2 | 2-1/4 | 276 | |

| Short Shank-For Insulators with standard 1" Threaded Pin Hole | | | | | | | | | | | |
|---|-----------------|-----|---|-------|-------|---|------------------|--|--|--|--|
| Catalog Number | Thread Material | Ø | < | В | Т | О | Weight/100 (lbs) | | | | |
| J222Z | Nylon Alloy | 5/8 | 6 | 2-1/2 | 2-3/8 | 2 | 104 | | | | |
| J224Z | Nylon Alloy | 3/4 | | | 1-5/8 | | | | | | |
| <u>J24365Z</u> | Nylon Alloy | 3/4 | 7 | 2-1/2 | 2-3/8 | 2 | 196 | | | | |

ISO Certification
©2018 MacLean Power Systems

About MPS | Customer Service | Industry Links | News | Careers | Contact Us Privacy Policy | Conflict Minerals Policy | Customer Terms | Supplier Terms | Site Map



Web site design and web site development by Americaneagle.com