



MPServiceNet

Login

- enter email -

- enter password -

[Forgot your password?](#)[Need an account?](#)

Online Catalog

MacLean Real-Time Design™

Anchors - Utility

Arresters

Conductor Hardware

Cutouts

Fiberglass - Utility

Safety Products

Transmission Insulators

Distribution Insulators

Substation Insulators

Pole Line Hardware A-E

Pole Line Hardware F-Z

Industry Links

Buy America Certified

## Also of Interest

[Conductor Hardware](#)[Anchors - Utility](#)[Cutouts](#)[About MPS](#) [Technical References](#) [Customer Service](#) [Distributor Locator](#) [Rep Locator](#) [Industry Links](#) [News](#) [Contact Us](#)

Search

Cross Reference

Keyword or Part #

[Anchors - Utility >> Power Hub Anchors](#)

1 1/2" (3.8 cm) Square Hub

[Print This Page](#) [Print PDF Catalog Page\(s\)](#)

## Features:

- Used for normal soils.
- Hub is 1.5 inch (3.8 cm) square and available in 2 torque ratings.
- Drive end of the standard power installed anchor installing tool torque tube with flared end for 1.5 inch (3.8 cm) hubs engages over the square hub
- All of the power installed anchor rods are used with this anchor

## Application:

- Assemble the rod to the hub
- Insert the anchor into the torque tube and fully engage to the tool locking assembly.
- Installed in line with the guy per the specific anchor instruction
- See [Rod with Eye nut](#) to select the appropriate rod and eye nut combination
- See [Rod with Coupling](#) for rod extensions
- See [Installation Tools](#) to select the appropriate torque tubes and other installing equipment
- For help selecting the appropriate Power Hub anchor click [here](#)
- Visit [MacLean Real Time Design™](#) to design the custom anchor that fits your needs

## Material:

- Coated with rust inhibitor



Solid Helix

Solid Hub



Twin Helix

Solid Hub

1-1/2" (3.8 cm) Square Solid Hub - 6,000 Ft- Lb. (8,135 N-m) Ultimate Installing Torque			
Catalog Number	Helix Size Inches (cm)	Tapped for Rod Size Inches (cm)	Weight Lbs (kg)
<a href="#">D182</a>	8 (20.3)	5/8 (1.6)	11 (5)
<a href="#">D184</a>	8 (20.3)	3/4 or 1 (1.9 or 2.5)	11 (5)
<a href="#">D1102</a>	10 (25.4)	5/8 (1.6)	14 (6.4)
<a href="#">D1104</a>	10 (25.4)	3/4 or 1 (1.9 or 2.5)	14 (6.4)
<a href="#">D1114</a>	12 (30.5)	3/4 or 1 (1.9 or 2.5)	17 (7.7)
<a href="#">D1134</a>	14 (35.6)	3/4 or 1 (1.9 or 2.5)	22 (10)
<a href="#">D284</a>	(2) 8 (20.3)	3/4 or 1 (1.9 or 2.5)	32 (14.5)

<a href="#">D2104</a>	(2) 10 (25.4)	3/4 or 1 (1.9 or 2.5)	38 (17.2)
-----------------------	---------------	-----------------------	-----------

1-1/2" (3.8 cm) Square Solid Hub - 7,000 Ft.-Lb. (9,490 N-m) Ultimate Installing Torque			
Catalog Number	Helix Size Inches (cm)	Tapped for Rod Size Inches (cm)	Weight Lbs (kg)
<a href="#">D184-7</a>	8 (20.3)	3/4 or 1 (1.9 or 2.5)	11 (5)
<a href="#">D1104-7</a>	10 (25.4)	3/4 or 1 (1.9 or 2.5)	15 (6.8)
<a href="#">D1114-7</a>	12 (30.5)	3/4 or 1 (1.9 or 2.5)	18 (8.2)
<a href="#">D244-7</a>	(2) 4 (10.2)	3/4 or 1 (1.9 or 2.5)	20 (9.1)
<a href="#">D284-7</a>	(2) 8 (20.3)	3/4 or 1 (1.9 or 2.5)	27 (12.2)
<a href="#">D2104-7</a>	(2) 10 (25.4)	3/4 or 1 (1.9 or 2.5)	32 (14.5)



ISO Certification  
©2018 MacLean Power Systems

About MPS | Customer Service | Industry Links | News | Careers | Contact Us  
Privacy Policy | Conflict Minerals Policy | Customer Terms | Supplier Terms | Site Map



Web site design and web site development by Americaneagle.com